

**AGILE PERFORMER.
UNSURPASSE
MANOEUVRABILITY.**

6075 N (4WD)
NARROW SERIES



FUNCTIONAL FEATURES



4-CYLINDER
ESCORTS CRDI ENGINE
FOR AN UNPARALLELED
POWERFUL PERFORMANCE



DRY AIR CLEANER
WITH CLOGGING SENSOR
TO ENSURE MINIMAL
MAINTENANCE



BATTERY CUT
OFF SWITCH
FOR AN IMPROVED
BATTERY LIFE



OIL-IMMERSED
BRAKES
FOR HIGH-EFFICIENCY
AND RELIABLE OPERABILITY



DESIGN FEATURES



STYLISH PROJECTOR LAMPS WITH LED DIGITAL INSTRUMENT CLUSTER



TELESCOPIC STEERING



DRIVER SEAT WITH OPS



AC CABIN

NARROWTRAC 6075 N OFFERS TOP-NOTCH PERFORMANCE WITH ITS 4-CYLINDER, TCI ENGINE COMBINED WITH 12+12 TRANSMISSION (24+24 - OPTIONAL). CHURNING OUT A MASSIVE POWER OF 75 HP @ 2200 RPM, THIS TRACTOR IS SPECIALLY DESIGNED FOR ORCHARDS AND VINEYARDS WITH A FRONT TRACK OF 1150 MM.

WHAT SETS IT APART IS ITS BEST-IN-CLASS MITA-MAKE HYDRAULIC LIFT THAT OFFERS A LIFTING CAPACITY OF UP TO 2500 KG. ADDING TO ITS UTILITY IS ITS AGILITY OWING TO THE 4WD FRONT AXLE AND BALANCED POWER STEERING WITH 3.3M TO 3.5M TURNING RADIUS.



6075 N (4WD)
NARROW SERIES



STEERING

Steering	Power Steering with Telescopic Column
----------	---------------------------------------

ENGINE

Power at Rated ERPm, HP (KW)	75HP @ 2200ERPm
Type - NA/ TC/TCI/CRDI	TCI
Swept Volume (cc)	3680
No of Cylinders	4
Max. Torque, Nm (+/- 100-200 rpm)	315 Nm at 1300-1400 rpm

3-POINT LINKAGES

3 point linkage (Geometry) category I / II	CatII
--	-------

HYDRAULICS

Functions	Draft & Position Control
Type & Lift Capacity (Kg)	2500
Auxiliary Valve	2DA/2SA Convertible

CAPACITIES (+/-5%)

Fuel Tank capacity, ltr.	70
--------------------------	----

DIMENSIONS (+/-5%)

Length, mm	4069
Width, mm	470 mm with 1094 mm Std. Track(1350-1890)
Height, mm	2578(ROPS)

PTO

PTO speed- Std	540/540E
PTO RPM @ Engine RPM	540 @ 1938 ERPm/540E @ 1648 ERPm

CLUTCH

Type	Double Clutch
------	---------------

BRAKES

Type	OIB
Hand Brake	Independent Parking Brake Lever

FRONT AXLE

Front Axle	4WD
------------	-----

VEHICLE

Air Cleaner type	Dry air cleaner
------------------	-----------------

TYRE

Front Tyre	8.00x18
Rear Tyre	14.9X24

TRANSMISSION

Type	Syncho mesh
No. of Gears	12F /12R
Rear Axle Reduction Type	EPI
Differential Lock	Yes